

# Myka FSR Comp 2012

## Technische Spezifikationen:

<b>RAHMEN</b>	M4 hydroformed women's tubesets, XC Trail geometry, sealed cartridge bearings, bolt-on cable guides, replaceable derailleur hanger, DMD mount, disc only, 100mm travel
<b>FEDERBEIN</b>	RockShox Ario RL, custom women's tune, rebound adj. and LO, 6.5x1.5"
<b>GABEL</b>	RockShox XC32, custom coil spring weights, alloy steerer, disc only mag lower, LO and rebound adj., preload adj., 100mm travel
<b>STEUERSATZ</b>	1-1/8" upper and lower Campy-style cartridge bearings for integrated alloy HT
<b>VORBAU</b>	Specialized XC, 3D forged alloy, 4-bolt, 31.8mm clamp, adjustable rise
<b>LENKER</b>	Specialized low-rise, 6061 butted alloy, 660mm wide, 8° backsweep, 6° upsweep, 31.8mm
<b>LENKERGRIFFE</b>	Specialized XC lock-on
<b>VORDERRADBREMSE</b>	Tektro Draco, hydraulic disc, ceramic pad compound, Caliper/Adapter w/Light Wave rotor, 160mm rotor
<b>HINTERBREMSE</b>	Tektro Draco, hydraulic disc, ceramic pad compound, Caliper/Adapter w/Light Wave rotor, 160mm rotor
<b>BREMSHEBEL</b>	Tektro Draco hydraulic
<b>UMWERFER</b>	Shimano SLX, E-type for DMD, top-swing, bottom-pull, M660E
<b>SCHALTWERK</b>	Shimano Alivio, 9-speed, SGS cage, M430
<b>SCHALTHEBEL</b>	Shimano Alivio M430, 9-speed, trigger, M430
<b>KASSETTE</b>	Shimano 9-speed, 11-34t, HG20
<b>KETTE</b>	KMC X-9, 9-speed, reusable Missing Link
<b>KURBELGARNITUR</b>	Shimano Alivio, Octalink spline, replaceable rings, S/M: 170mm, L: 175mm
<b>KETTENBLÄTTER</b>	42/32/22
<b>INNENLAGER</b>	Shimano, Octalink spline, cartridge bearing, 73mm
<b>PEDALE</b>	Alloy platform, 9/16"
<b>FELGEN</b>	Alex RHD 26", alloy disc, double-wall, pin joint, eyelets, 24mm, 32h
<b>VORDERRADNABE</b>	Specialized Hi Lo disc, loose ball, machined disc, 32h, QR
<b>HINTERRADNABE</b>	Specialized Hi Lo disc, double-sealed cartridge bearing, QR, 32h
<b>SPEICHEN</b>	Stainless, 1.8mm (15g)
<b>VORDERREIFEN</b>	Specialized The Captain Sport, 60 TPI, wire bead, 26x2.0"
<b>HINTERREIFEN</b>	Specialized The Captain Sport, 60 TPI, wire bead, 26x2.0"
<b>SCHLÄUCHE</b>	Schrader valve
<b>SATTEL</b>	Specialized Women's Body Geometry Riva, 143mm
<b>SATTELSTÜTZE</b>	6061 alloy, 2-bolt micro adjust, setback head, 30.9mm, 350mm
<b>SATTELSTÜTZKLEMME</b>	34.9mm clamp ID, 7050 hard anodized alloy collar w/ QR, black

Änderungen von Spezifikationen vorbehalten.

## Geometrie

Größe	S	M	L
Bottom Bracket Height - Low Setting	330mm	330mm	330mm
Chainstay Length	420mm	420mm	420mm
<b>TT Oberrohrlänge ist horizontal gemessen von Mitte-Steuerrohr bis Mitte-Sitzrohr nach unserer Messung 25-30mm kürzer!</b>			
Crank Length	170mm	170mm	175mm
Ground-Top	870mm	888mm	898mm
Handlebar Width	640mm	640mm	660mm
Head Tube Angle - Low Setting	68.5°	68.5°	68.5°
Head Tube Height	110mm	130mm	140mm
Reach	392mm	410mm	448mm
Seat Tube Angle (Actual) - Low Set	71°	71°	71°
Seat Tube Angle (Effective) - Low S	74.5°	74.5°	74.5°
Seat Tube Length - Center to Top	394mm	431mm	470mm
Seatpost Length	350mm	350mm	350mm
Stack	540mm	558mm	568mm
Standover Height	674mm	676mm	682mm
Stem Length	60mm	75mm	75mm
Top Tube Length (Actual)	509mm	529mm	567mm
Top Tube Length (Horizontal)	542mm	565mm	605mm
Wheel Base	1063mm	1088mm	1129mm