

Safire FSR Pro 2012

Technische Spezifikationen:

RAHMEN	Specialized Safire M5 alloy frame, Women's XC Trail Geometry, tapered HT, DMD front derailleur, sealed cartridge bearing pivots, replaceable derailleur hanger, disc only, bolt-on cable guides with Brain mount on SS, 120mm travel
FEDERBEIN	Specialized/FOX Brain Shock w/ remote Safire Tune inertia valve, Brain Fade and rebound adj., 6.5x1.45", integrated cartridge bearing shock mount
GABEL	Specialized Future Shock S140TA, Spike Valve damper, tapered carbon steer/crown, comp and rebound adj., low bearing mount, 140/115mm travel adjust
STEUERSATZ	1-1/8 and 1-1/2" threadless, Campy style upper with 1-1/2" lower, cartridge bearings
VORBAU	Specialized XC, 3D forged alloy, 4-bolt, adj. rise, 31.8mm clamp
LENKER	Specialized XC low-rise bar, 7050 butted alloy, 680mm wide, 8-degree backsweep, 6-degree upsweep, 31.8mm
LENKERGRIFFE	Specialized Women's Enduro, lock-on
VORDERRADBREMSE	Custom Avid Elixir 7 SL, hydraulic disc, pad contact & reach adj., alloy backed semi-metallic pads, stainless hardware,
HINTERBREMSE	Custom Avid Elixir 7 SL, hydraulic disc, pad contact & reach adj., alloy backed semi-metallic pads, stainless hardware,
BREMSHEBEL	Custom Avid Elixir 7 SL, hydraulic disc, tool-less reach and pad contact adj., alloy lever blade
UMWERFER	SRAM X7, 10-speed, S1 direct mount for DMD, bottom pull
SCHALTWERK	SRAM X0, 10-speed, mid cage
SCHALTHEBEL	SRAM X9, 10-speed, trigger
KASSETTE	Shimano XT 10-speed, 11-36t, M771
KETTE	KMC X10, nickel plate, reusable Missing Link
KURBELGARNITUR	Custom SRAM carbon S-2200, 10-speed XC Trail double, GXP spindle, carbon guard, S: 165mm, MD: 170mm, LG: 175mm
KETTENBLÄTTER	36/22, carbon guard
INNENLAGER	SRAM GXP, outboard bearing
PEDALE	Resin Test Ride Pedals with toe clips, CEN std.
FELGEN	Roval Control, alloy disc, 24mm, 24/28h
VORDERRADNABE	Roval Control, OS 28mm end caps, QR, 24h
HINTERRADNABE	Roval Control, DT Swiss alloy cassette body, QR, 28h
SPEICHEN	Roval Control
VORDERREIFEN	Specialized Purgatory Control, 2Bliss Ready, 120 TPI, aramid bead, dual-compound, 26x2.2"
HINTERREIFEN	Ground Control, 2Bliss Ready, 60 TPI, 2Bliss ready aramid bead, 26x2.1"
SCHLÄUCHE	Ultralight presta valve
SATTEL	Specialized Women's Body Geometry Ariel Comp, hollow Cr-Mo rails, 143mm
SATTELSTÜTZE	Specialized Command Post BlackLite, 3 position, adjustable height w/air spring, remote operated, single bolt head 30.9r
SATTELSTÜTZKLEMME	34.9mm clamp ID, single bolt alloy collar

Änderungen von Spezifikationen vorbehalten.

Geometrie

Größe	XS	S	M	L
Bottom Bracket Height - High Setting	353mm	353mm	353mm	353mm
Bottom Bracket Height - Low Setting	343mm	343mm	343mm	343mm
Chainstay Length	421mm	421mm	421mm	421mm
Crank Length	165mm	165mm	165mm	165mm
Ground-Top	936mm	936mm	936mm	936mm
Handlebar Width	750mm	750mm	750mm	750mm
Head Tube Angle - High Setting	64.8°	64.8°	64.8°	64.8°
Head Tube Angle - Low Setting	64°	64°	64°	64°
Head Tube Height	112mm	112mm	112mm	112mm
Reach	390mm	410mm	430mm	447mm
Seat Tube Angle (Actual) - High Set	62.8°	62.8°	62.8°	62.8°
Seat Tube Angle (Actual) - Low Set	62°	62°	62°	62°
Seat Tube Angle (Effective) - High S	76.8°	76.8°	76.8°	76.8°
Seat Tube Angle (Effective) - Low S	76°	76°	76°	76°
Seat Tube Length - Center to Top	394mm	394mm	419mm	458mm
Seatpost Length	300mm	300mm	300mm	300mm
Stack	593mm	593mm	593mm	593mm
Standover Height	717mm	717mm	722mm	731mm
Stem Length	50mm	50mm	50mm	50mm
Top Tube Length (Actual)	485mm	504mm	517mm	530mm
Top Tube Length (Horizontal)	540mm	560mm	580mm	597mm
Wheel Base	1151mm	1171mm	1191mm	1208mm