

# Safire Comp 2013

## Technische Spezifikationen:

<b>RAHMEN</b>	Specialized Safire M5 alloy frame, Women's XC Trail Geometry and tubesets, tapered HT, DMD front derailleur, sealed cartridge bearing pivots, replaceable derailleur hanger, bolt-on cable guides with Brain mount on SS, 120mm travel
<b>DÄMPFER</b>	Custom FOX Float CTD Evolution with AUTOSAG for Safire, Climb, Trail, Descend settings and rebound adj., 165x38mm
<b>GABEL</b>	FOX Float CTD Evolution 26, air spring, tapered steerer, Climb, Trail, Descend settings and reb adj., standard QR dropout, 120mm travel
<b>STEUERSATZ</b>	1-1/8 and 1-1/2" threadless, Campy style upper with 1-1/2" lower, cartridge bearings
<b>VORBAU</b>	Specialized, alloy, adj. rise, 31.8mm clamp
<b>LENKER</b>	Specialized XC low-rise bar, 7050 butted alloy, 680mm wide, 8-degree backsweep, 6-degree upsweep, 31.8mm
<b>LENKERGRIFFE</b>	Specialized Women's Enduro, lock-on
<b>VORDERRADBREMSE</b>	Custom Avid Elixir 5 SL, alloy backed organic pads, HS-1 rotor, 160mm rotor
<b>HINTERRADBREMSE</b>	Custom Avid Elixir 5 SL, alloy backed organic pads, HS-1 rotor, 160mm rotor
<b>BREMSHEBEL</b>	Custom Avid Elixir 5 R SL, hydraulic disc, tool-less reach adj.
<b>UMWERFER</b>	SRAM X7, 10-speed, S3 direct mount for DMD, bottom pull
<b>SCHALTWERK</b>	SRAM X9 Type 2, 10-speed, mid cage
<b>SCHALTHEBEL</b>	SRAM X7, 10-speed, trigger, w/MatchMaker clamp
<b>KASSETTE</b>	SRAM PG-1030, 10-speed, 11-36
<b>KETTE</b>	KMC X10, nickel plate, reusable Missing Link
<b>KURBELGARNITUR</b>	Custom SRAM S-1250, 7050 alloy arms, 10-speed XC double, GXP spindle, SM: 165mm, MD: 170mm, LG: 175mm
<b>KETTENBLÄTTER</b>	36/22, alloy guard
<b>INNENLAGER</b>	SRAM GXP, outboard bearing
<b>PEDALE</b>	Resin Test Ride Pedals with toe clips, CEN std.
<b>FELGEN</b>	Custom DT Swiss X420SL, 24mm wide, 28/32h
<b>VORDERRADNABE</b>	Specialized Hi Lo disc, OS28 end caps, sealed cartridge bearing, QR, 32h
<b>HINTERRADNABE</b>	Specialized Hi Lo disc, 4x-sealed cartridge bearing, QR, 32h
<b>SPEICHEN</b>	DT Swiss Industry, stainless, stainless
<b>VORDERREIFEN</b>	Specialized Purgatory Control, 2Bliss Ready, 60vTPI, aramid bead, dual-compound, 26x2.3"
<b>HINTERREIFEN</b>	Ground Control, 2Bliss Ready, 60 TPI, wire bead, 26x2.1"
<b>SCHLÄUCHE</b>	Ultralight presta
<b>SATTEL</b>	Specialized Women's Body Geometry Ariel Comp, hollow Cr-Mo rails, 143mm
<b>SATTELSTÜTZE</b>	Specialized 2014 butted alloy, single bolt setback, 30.9mm, 350mm
<b>SATTELSTÜTZKLEMME</b>	Specialized 7050 hard anodized alloy, 32.6mm, single bolt

Änderungen von Spezifikationen vorbehalten.

## Geometrie

Größe	S	M	L
Bottom Bracket Height - Low Setting	338mm	338mm	338mm
Chainstay Length	420mm	420mm	420mm
Crank Length	165mm	170mm	175mm
Ground-Top	885mm	904mm	913mm
Handlebar Width	680mm	680mm	680mm
Head Tube Angle - Low Setting	68.5°	68.5°	68.5°
Head Tube Height	110mm	130mm	140mm
Reach	388mm	408mm	440mm
Seat Tube Angle (Actual) - Low Sett	70.5°	70.5°	70.5°
Seat Tube Angle (Effective) - Low S	74.5°	74.5°	74.5°
Seat Tube Length - Center to Top	394mm	431mm	470mm
Seatpost Length	350mm	350mm	350mm
Stack	547mm	566mm	575mm
Standover Height	688mm	689mm	695mm
Stem Length	60mm	75mm	75mm
Top Tube Length (Actual)	505mm	527mm	559mm
Top Tube Length (Horizontal)	540mm	565mm	600mm
Wheel Base	1066mm	1093mm	1129mm
Top Tube Length (Horizontal)	540mm	560mm	580mm
Wheel Base	1151mm	1171mm	1191mm