

Stumpjumper FSR Comp Carbon 29 2013

Technische Spezifikationen:

RAHMEN	FACT IS 9m carbon front triangle, 29" geometry, M5 alloy rear triangle, tapered HT, carbon PF30 BB, ISCG '05, internal Command Post routing, 142mm dropouts, sealed cartridge bearing pivots, replaceable derailleur hanger, 130mm travel
DÄMPFER	Custom FOX Float CTD Evolution with AUTOSAG, Climb, Trail, Descend settings and rebound adj., 194x48mm
GABEL	FOX Float CTD Evolution 29, air spring, tapered steerer, Climb, Trail, Descend settings and reb adj., 15mm thru-axle, 130mm travel
STEUERSATZ	1-1/8 and 1-1/2" threadless, Campy style upper with 1-1/2" lower, cartridge bearings
VORBAU	Specialized XC Trail, 6061 alloy, 4-bolt, 6-degree rise, 31.8mm
LENKER	Specialized XC Mini-Riser, 7050 butted alloy, 720mm wide, 10mm rise, 10-degree backsweep, 6-degree upsweep, 31.8mm
LENKERGRIFFE	Specialized Sip Grip, half-waffle aramid-infused, S/M: Regular, Others: XL thickness
VORDERRADBREMSE	Custom Avid Elixir 5 SL, hydraulic disc, alloy backed organic pads, HS-1 rotor. S/M: 180mm; L/XL 200mm rotor
HINTERRADBREMSE	Custom Avid Elixir 5 SL, hydraulic disc, alloy backed organic pads, HS-1 rotor. S/M: 160mm; L/XL 180mm rotor
BREMSHEBEL	Custom Avid Elixir 5 R SL, tool-less reach adj.
UMWERFER	SRAM X7, 10-speed, S3 direct mount for DMD, bottom pull
SCHALTWERK	Shimano XT Shadow Plus, 10-speed, SGS long cage
SCHALTHEBEL	Shimano SLX 10-speed, trigger
KASSETTE	SRAM PG-1030, 10-speed, 11-36
KETTE	KMC X10, nickel plate, reusable Missing Link
KURBELGARNITUR	Custom SRAM S-1250, 10-speed XC Trail double w/ alloy guard, PF30 spindle, S: 170mm, Others: 175mm
KETTENBLÄTTER	36/22, w/ alloy guard
INNENLAGER	SRAM PF30, OS press-in bearing, sealed cartridge
PEDALE	Resin Test Ride Pedals with toe clips, CEN std.
FELGEN	Roval 29, alloy disc, 26mm wide, 32h
VORDERRADNABE	Specialized Hi Lo disc, sealed cartridge bearing, 15mm thru-axle, 32h
HINTERRADNABE	New Specialized Hi Lo disc, 4x-sealed cartridge bearing, 142mm spacing, 12mm thru-axle, 32h
SPEICHEN	DT Industry, 2.0 stainless
VORDERREIFEN	Specialized Purgatory Control, 2Bliss Ready, 60TPI, aramid bead, dual-compound, 29x2.3"
HINTERREIFEN	Specialized Ground Control, 2Bliss Ready, 60TPI, aramid bead, 29x2.3"
SCHLÄUCHE	Ultralight presta
SATTEL	Body Geometry Henge Comp, hollow Cr-Mo rails, 143mm
SATTELSTÜTZE	Specialized 2014 butted alloy, single bolt setback, 30.9mm, S/M: 350mm, Others: 400mm
SATTELSTÜTZKLEMME	34.9mm clamp, 7050 hard anodized alloy collar w/ QR, black

Änderungen von Spezifikationen vorbehalten.

Geometrie

Größe	S	M	L	XL
Bottom Bracket Drop	34mm	34mm	34mm	34mm
Bottom Bracket Height	338mm	338mm	338mm	338mm
Chainstay Length	450mm	450mm	450mm	450mm
Crank Length	170mm	175mm	175mm	175mm
Handlebar Width	720mm	720mm	720mm	720mm
Head Tube Angle	69°	69°	69°	69°
Head Tube Length	90mm	100mm	125mm	145mm
Reach	399mm	427mm	445mm	466mm
Seat Tube Angle, Actual	69°	69.4°	69.8°	70.3°
Seat Tube Angle, Effective	74.5°	74.5°	74.5°	74.5°
Seat Tube Length, Center to Top	396mm	430mm	468mm	523mm
Seatpost Length	380mm	425mm	425mm	425mm
Stack	605mm	614mm	638mm	656mm
Standover Height	750mm	741mm	750mm	764mm
Stem Length	60mm	75mm	90mm	90mm
Top Tube Length, Actual	576mm	603mm	632mm	660mm
Top Tube Length, Horizontal	567mm	596mm	622mm	648mm
Wheel Base	1117mm	1147mm	1175mm	1203mm