

Epic Comp Carbon 29 2014

Technische Spezifikationen:

RAHMEN	FACT 9m carbon front triangle, SWAT EMT tool cradle, 29" geometry, FACT IS construction, M5 rear triangle, tapered headtube, carbon PF30 BB, full internal shift/brake routing, 142mm
DÄMPFER	FOX/Specialized remote Mini-Brain w/ AUTOSAG, inertia valve w/ Kevlar hose, Brain Fade adjust, 205x53mm, 100mm travel
GABEL	RockShox Reba RL 29, Solo Air spring, alloy tapered steerer, lockout and reb adj., 15mm thru-axle, 100mm travel
STEUERSATZ	1-1/8 and 1-1/2" threadless, Campy style upper with 1-1/2" lower, cartridge bearings
VORBAU	Specialized XC, 3D forged alloy, 4-bolt, 6-degree rise, 31.8mm clamp
LENKER	Specialized XC, flat bar, 2014 butted alloy, 700mm wide, 8-degree backsweep, 31.8mm
LENKERGRIFFE	Specialized Sip Grip, light lock-on, half-waffle aramid-infused, S/M: regular, Others: XL thickness
VORDERRADBREMSE	Formula C1, alloy caliper, metallic pad, S/M: 160mm, L/XL: 180mm rotor
HINTERRADBREMSE	Formula C1, alloy caliper, metallic pad, 160mm rotor
BREMSHEBEL	Formula C1, hydraulic disc, tooled reach adj.
UMWERFER	Custom SRAM, 10-speed, high direct-mount
SCHALTWERK	Shimano XT Shadow Plus, 10-speed, SGS long cage
SCHALTHEBEL	Shimano SLX, 10-speed, trigger
KASSETTE	SRAM PG-1030, 10-speed, 11-36
KETTE	SRAM PC 1031, 10-speed, PowerLink
KURBELGARNITUR	Custom SRAM S-1250, 7050 alloy arms, 10-speed XC double, PF30 spindle, S: 170mm, Others: 175mm
KETTENBLÄTTER	38A x 24A, 4-bolt, 104/64mm
INNENLAGER	SRAM PF30, OS press-in bearings, sealed cartridge
PEDALE	Resin Test Ride Pedals with toe clips, CEN std.
FELGEN	Roval 29, alloy disc, 22mm internal width, 32h
VORDERRADNABE	Specialized Hi Lo disc, sealed cartridge bearings, 15mm thru-axle, 32h
HINTERRADNABE	Specialized Hi Lo disc, 4x-sealed cartridge bearings, 12mm thru-axle, 142+ spacing, 32h
SPEICHEN	DT Industry Stainless, 3X front/rear 2.0
VORDERREIFEN	S-Works Fast Trak, 2Bliss Ready, 29x2.0", foldable aramid bead, 120 TPI
HINTERREIFEN	Specialized Fast Trak Control, 2Bliss Ready, 29x2.0", foldable aramid bead, 60 TPI
SCHLÄUCHE	Ultralight presta
SATTEL	Body Geometry Phenom Comp, hollow Cr-Mo rails, 143mm
SATTELSTÜTZE	Specialized 2014 butted alloy, single bolt setback, 27.2mm, S/M: 350mm, Others: 400mm
SATTELSTÜTZKLEMME	Specialized 7050 hard anodized alloy, single bolt, 31.8mm

Änderungen von Spezifikationen vorbehalten.

Geometrie

Größe	S	M	L	XL
Hinterbaulänge (mm)	448mm	448mm	448mm	448mm
Lenkerbreite	700mm	700mm	700mm	700mm
Lenkwinkel	70.5°	70.5°	70.5°	70.5°
Oberrohrlänge horizontal	564mm	593mm	620mm	647mm
Oberrohrlänge tatsächlich	559mm	587mm	614mm	642mm
Radstand	1082mm	1112mm	1140mm	1168mm
Reach	393mm	418mm	441mm	462mm
Sitzrohrlänge	350mm	400mm	400mm	400mm
Sitzrohrlänge (Mitte Tretl. bis Ende)	400mm	434mm	470mm	520mm
Sitzrohrwinkel effektiv	73.75°	68.9°	73.75°	69.25°
Sitzrohrwinkel effektiv	69.6°	73.75°	70°	73.75°
Stack	587mm	601mm	615mm	634mm
Steuerrohrlänge	90mm	105mm	120mm	140mm
Tretlagerabsenkung	40mm	40mm	40mm	40mm
Tretlagerhöhe	332mm	332mm	332mm	332mm
Vorbaulänge	170mm	75mm	90mm	175mm
Vorbaulänge	175mm	100mm	110mm	175mm
Überstandshöhe (mm)	770mm	774mm	780mm	793mm