

Rumor Comp 29 2014

Technische Spezifikationen:

RAHMEN	Specialized Rumor M5 hydroformed alloy frame, Women's XC Trail 29er Geometry and tubesets, tapered headtube, Command Post routing, DMD mounts, SRAM FD adapter, 110mm travel
DÄMPFER	Custom Monarch RL w/ AUTOSAG for Rumor, air spring, custom tune, lockout, rebound adj., 197x48mm
GABEL	RockShox Reba RL 29, Solo Air spring, tapered alloy steerer, rebound adj., standard QR dropouts, 110mm travel
STEUERSATZ	1-1/8 and 1-1/2" threadless, Campy style upper w/ 1-1/2" lower, cartridge bearings, alloy flush top bearings cap
VORBAU	Specialized, alloy, adjustable rise, 31.8mm clamp
LENKER	Specialized XC mini-riser, 7050 butted alloy, 680mm wide, 10mm rise, 10-degree backsweep, 6-degree upsweep, 31.8mm
LENKERGRIFFE	Specialized Women's Enduro, lock-on
VORDERRADBREMSE	Custom Avid Elixir 5 SL, alloy-backed organic pads, HS-1 rotor, 160mm rotor
HINTERRADBREMSE	Custom Avid Elixir 5 SL, alloy-backed organic pads, HS-1 rotor, 160mm rotor
BREMSHEBEL	Custom Avid Elixir 5 R SL, hydraulic lever, tool-less reach adj.
UMWERFER	SRAM X7, 10-speed, S3 direct mount for DMD, bottom-pull
SCHALTWERK	SRAM X9 Type 2, 10-speed, mid cage
SCHALTHEBEL	SRAM X7, 10-speed, trigger, w/ MatchMaker clamp
KASSETTE	SRAM PG-1030, 10-speed, 11-36
KETTE	KMC X10, nickel plate, reusable Missing Link
KURBELGARNITUR	Custom SRAM S-1250, 7050 alloy arms, 10-speed Trail double, PF30 spindle, S: 165mm, M: 33/22
KETTENBLÄTTER	
INNENLAGER	SRAM PF30, OS press-in bearings, sealed cartridge
PEDALE	Resin test ride w/ toe clips, CEN std.
FELGEN	Roval 29, alloy disc, 26mm wide, 32h
VORDERRADNABE	Specialized Hi Lo disc, OS28 end caps, sealed cartridge bearings, 9mm QR, 32h
HINTERRADNABE	Specialized Hi Lo disc, 4x-sealed cartridge bearings, 12mm thru-axle, 32h
SPEICHEN	DT Swiss Industry, stainless, 14g
VORDERREIFEN	Specialized Ground Control, 2Bliss Ready, 29x2.3", aramid bead, 60TPI
HINTERREIFEN	Specialized Ground Control, 2Bliss Ready, 29x2.1", aramid bead, 60TPI
SCHLÄUCHE	Ultralight presta valve
SATTEL	Specialized Body Geometry Jett Comp Gel, hollow Cr-Mo rails, 143mm
SATTELSTÜTZE	Specialized 2014 butted alloy, single bolt, 30.9mm, S/M: 350mm, L: 400mm
SATTELSTÜTZKLEMME	Specialized 7050 hard anodized alloy, single bolt, 32.6mm

Änderungen von Spezifikationen vorbehalten.

Geometrie

Größe	S	M	L
Gesamthöhe bis Oberkante Steuerk	926mm	932mm	941mm
Hinterbaulänge (mm)	450mm	450mm	450mm
Lenkerbreite	680mm	680mm	680mm
Lenkwinkel - flache Einstellung	70°	70°	70°
Oberrohrlänge horizontal	545mm	570mm	595mm
Oberrohrlänge tatsächlich	517mm	536mm	559mm
Radstand	1089mm	1114mm	1139mm
Reach	388mm	411mm	433mm
Sitzrohrlänge	350mm	350mm	350mm
Sitzrohrlänge (Mitte Tretl. bis Ende)	387mm	427mm	445mm
Sitzrohrwinkel effektiv - flache Einst	75.09°	74.78°	74.66°
Sitzrohrwinkel tatsächlich - flache Ei	70°	70°	70°
Stack	595mm	600mm	610mm
Steuerrohrhöhe	94mm	100mm	110mm
Tretlagerhöhe - niedrige Einstellung	331mm	331mm	331mm
Vorbaulänge	165mm	60mm	170mm
Vorbaulänge	75mm	75mm	175mm
Überstandshöhe (mm)	706mm	709mm	710mm